

- Diesel-Resistant Elastomeric Polyolefin
- Superior protection from aviation & diesel fuels, hydraulic fluids, greases and lubricants.

Diesel-Resistant Heat Shrink Tubing

Product Number BD390

BD390 is a heat shrinkable, flame retarded, elastomer tubing specially formulated for long term resistance to fluids, heat and mechanical abuse.

Recommended for protecting cables and wire harnesses on military ground vehicles and is used in a variety of applications requiring ruggedness and fluid resistance.

BD390 remains flexible at low temperatures which makes it ideal for cables and harness applications that operate in severe environmental conditions.



Flexible, abrasion resistant covering for wires

Specifications:

<u>Order Size</u>	<u>Expanded Diameter</u>	<u>Recovered Diameter</u>	<u>Recovered Wall</u>
1/8"	.125	.062	.028
3/16"	.187	.093	.031
1/4"	.250	.125	.035
3/8"	.375	.187	.039
1/2"	.500	.250	.047
3/4"	.750	.375	.059
1"	1.000	.500	.071
1-1/2"	1.500	.750	.094
2"	2.000	1.000	.110

M23053/16

Temperature Ratings: -75°C to +120°C

Shrink Temperature: 150°C minimum

Standard Color: Black

Markers and Cut Pieces Available

